

S520

PORTABLE DEW POINT METER

(-100 ... +50 °C TD)



Smart DEVICE
Dew point prediction

ISO-8573



Ultra portable — All in one single handheld



S520 FEATURES



SMART DEVICE

Dew point
prediction




TOUCH SCREEN

Intuitive
user interface



PRESSURE SENSOR

Enables various
humidity units



DATA LOGGER

Integrated
mass storage



LOW DEW POINT

Measures
down
to -100 °C Td



CAMERA INTEGRATED

Pictures for
better reports



PORTABLE UNIT

Handheld unit
within a rugged
case



DEW POINT AUDITS

Indication of
class on display

S520 BENEFITS

- Measures dew point, temperature and pressure in one device
- Sensor selection according to your needs:
 - 100 ... +20 °C Td with pressure sensor as standard version
 - 50 ... +50 °C Td without pressure sensor as economic version
- Easy to use, but powerful performance
- Optional smart features: End value prediction, camera and measurement snapshot
- Wireless printer for on-site reporting, perfect for audits
- Unique Measuring chamber with parking function as standard included

DEW POINT PREDICTION

The S520 offers a unique dew point end value prediction algorithm as a built-in technology.

Based on the dew point measurement curve our algorithm is able to predict the end value before actually reaching the end value.

This feature enables the user to predict the dew point end value in a minimum amount of time. It helps on-site engineers to save time and to perform faster dew point audits.

Dew point end value prediction is a part of the smart features. With the smart features option, users also get a 5 Megapixel camera and the snapshot function for quick measurement logging.

S520 TECHNICAL DATA

General Specification		
Measuring range	Standard: -100 ... +20 °C Td Economic: -50 ... +50 °C Td Pressure*: 0 ... 1.5 MPa(g) Temperature: -30 ... +50 °C	
Dew Point Sensor	Sensor A1370: QCM + Polymer ; Sensor A1371: Polymer	
Temperature Sensor	Pt100	
Pressure Sensor	Piezo resistive type (only with Sensor A1370)	
Accuracy	Dew point: +/- 1 °C Td (0 ... 20 °C Td) +/- 2 °C Td (-60 ... 0 °C Td / +20 ... +50 °C Td) +/- 3 °C Td (-100 ... -60 °C Td)	Temperature: +/- 0.3 °C Pressure: 0.5 % FS
Measured units (selectable)	°C Td • g/m ³ • mg/m ³ • g/m ³ atm (@zero pressure) • mg/m ³ atm (@zero pressure) • ppmv • g/kg (@ reference pressure) • °C Tdatm (@ zero pressure) • % RH	
Operating Pressure	-0.1 ... 1.5 MPa(g) (at least 0.3 MPa is needed for the measuring chamber supplied with the instrument)	
Measured gas (Medium)	Air, CO ₂ , N ₂ , O ₂ , Argon (CO ₂ measurements with the A1371 module are limited to -40 °C Td)	
Operating Parameters	Medium Temperature: -30 ... +50 °C / Ambient Temperature: 0 ... +40 °C / Ambient Humidity: 0 ... 80 % rH	
Housing material	PC + ABS	
Transport & Storage	Transport Temperature: -30 ... +50 °C / Storage Temperature: -20 ... +50 °C	
Weight	2.7 kg (complete set in transport case)	
Process Connection	G1/2" for direct sensor connection, Measuring chamber with 6 mm hose quick coupling	
Battery	Operating time on one charge: ~8 h / Charging time until full: ~3 h	
Interface	USB-C (charging and data transfer), wireless printer	
Display	3.5" color LCD Touch screen	
Camera	5.0 Megapixel (only with smart features option)	
Logger	Integrated mass storage, 100 Mio. values	

*at least 0.3 MPA is needed for the measuring chamber supplied with the instrument. For low pressure measurements below 0.3 MPa please choose the by-pass measuring chamber A699 3501.

Scope of delivery



S520



PTFE hose with quick connect



Unique measuring/parking chamber for fast sensor response



Option: wireless printer used to print the measurement results on site. Perfect solution for quick audits.



Memory stick



USB charger with USB-C cable



The included transport case protects the measurement instrument. At the same time it holds all accessories.

S520 ORDERING

Please use the following tables to assist in placing your order with our sales staff.

S520 PORTABLE DEW POINT METER		
Order No.	Code	Description
P600 0520	S520	S520 Handheld meter with data logger - Measuring chamber with parking function - USB-OTG memory stick - 1.5 m PTFE hose 6 mm with quick coupling, - Certificate of calibration - USB charger with USB-C cable - Transport casing
Measuring range (Sensor unit)		
A1370	A	-100 ... +20 °C Td Standard range sensor unit, with integrated pressure sensor -0.1 ... 1.5 MPa
A1371	B	-50 ... +50 °C Td Economic range sensor unit, without integrated pressure sensor
Wireless printer		
	A	Without printer
A1372	B	With wireless printer for measurement printouts on site
Smart features		
	A	Without smart features
A1373	B	With smart features (Measurement snapshot, Dew point end value prediction, Camera)

Example: S520ABB

S520 Handheld meter with data logger, measuring chamber, incl. transport casing, -100 ... +50 °C Td Standard range sensor unit with pressure measurement, wireless printer, smart features

S520 PORTABLE DEW POINT METER ACCESSORIES	
Order No.	Description
A699 3501	By-pass measuring chamber with parking function, 0 ... 1.0 MPa, 6 mm hose quick connector as in- and outlet
A554 0021	Paper rolls for wireless printer

大華高科股份有限公司

www.taiwah.com.tw

info@taiwah.com.tw

台北
台中
台南

TEL: (02) 2592 - 5119

TEL: (04) 2707 - 2269

TEL: (06) 243 - 2338

Fax: (02) 2592- 3577

Fax: (04) 2707- 1799

Fax: (06) 243 - 2339